

Address: No.2204, COFCO Property Tower ,No. 3 Area, Baoan District,Shenzhen,China. Tel: (86 755) 27758761 Fax: (86 755) 27758727
www.corelinkcn.com & www.globalsources.com/corelink.co
www.corelink.en.alibaba.com

Contact: Sophia Skype: corelinksales
 MSN/Email : sales1@corelinkcn.com

MINI DVB-T2 Receiver



NOT ONLY A SET TOP BOX, BUT ALSO A FAMILY MEDIA PLAYER

Item No.	Solution	Support	QTY	Sample	1000	3000	5000	8000	AC-3 DOBLY
HDT-003	Mstar7816	HDMI1.3 & 1080p	FOB Shenzhen	US\$38.00	US\$29.00	US\$28.50	US\$28.00	US\$27.50	+USD\$1

Specification

<p>Feature :</p> <ol style="list-style-type: none"> Fully SD/HD DVB-T/T2, SD/HD MPEG2 and MPEG4 AVC H.264 Full HD, support up to 1080P Auto and manually scan all available TV and radio channels Aspect ratio 16:9 and 4:3 HDMI, YUV, RCA, coaxial output Multi-language subtitle output supported Powerful and highly effective 7-day EPG function Supports teletext Parental lock PVR, timeshift via USB 2.0 Multimedia playback and software upgrade via USB 2.0 Stores up to 1,000 programs <p>Tuner</p> <p>RF input frequency: 44-1002Mhz Bandwith: 6/7/8MHz Input level: -83dBm Signal input: IEC-type female</p> <p>Chipset: MSTAR 7816</p> <p>Mpeg transport stream and A/V decoding Video standard: MPEG-4 AVC/H.264 HP@L4 SCART video model CVBS/RGB (for Europe) Aspect ratio: 4:3, 16:9 Video resolution: 576i, 576p, 720p and 1080i, 1080P</p> <p>Audio standard: ISO/IEC 14.496-3, AAC, AAC+ Audio mode: mono, dual-channel, stereo</p>	<p>Multimedia format:</p> <p>Picture: JPEG, BMP, PNG Audio: MP3, WMA Video: MKV, AVI, DIVX, XVID, MOV, VOB, FLV 3GP, DAT, MPEG, MPG, MP4, TS, TRP ...</p> <p>Input Voltage 5V Adaptor Real Standby <1watt Power consumption 8W (max) , USB :for firmware upgrade, PVR, multimedia playback</p> <p>Demodulation: QPSK, 16QAM, 64QAM, 256QAM Code Rate: 1/2, 3/5, 2/3, 3/4, 4/5, 5/6 Guard: from 1/128 to 1/4 FFT Mode: from 1K to 32K</p> <p>Standard</p> <p>DVB-T(ETSI EN 300 744) DVB-T2(ETSI EN 302 755)</p> <p>Rear panel output</p> <p>HDMI 576i, 576p, 720p and 1080i, 1080P</p> <p>Loop through output: IEC-type, connector, single tuner Coaxial: RCAX1 YpbPr RCAX3 L/R audio RCAX2 CVBS SCART(optional)</p>																								
<p>Packing:</p> <p>Export carton details</p> <table border="0"> <tr> <td>Packaging</td> <td>1</td> <td>Gift Box</td> </tr> <tr> <td>Qty per export carton</td> <td>20 pcs</td> <td>Pieces</td> </tr> <tr> <td>Gift box meas.:</td> <td>160 x 55 x 11</td> <td>MM</td> </tr> <tr> <td>Meas. per export carton</td> <td>355 x 295 x 31</td> <td>MM</td> </tr> <tr> <td>G.W:</td> <td>8.1</td> <td>Kgs</td> </tr> <tr> <td>N.W:</td> <td>7.6</td> <td>Kgs</td> </tr> </table>	Packaging	1	Gift Box	Qty per export carton	20 pcs	Pieces	Gift box meas.:	160 x 55 x 11	MM	Meas. per export carton	355 x 295 x 31	MM	G.W:	8.1	Kgs	N.W:	7.6	Kgs	<table border="0"> <tr> <td>Qty. per 20' container</td> <td>16,520</td> </tr> <tr> <td>Qty. per 40' container</td> <td>33,040</td> </tr> <tr> <td>Qty. per 40' HQ container</td> <td>37,040</td> </tr> </table> <p>Accessories R/C, User Manual, RCA cable, Adaptor(5V) User manual English</p>	Qty. per 20' container	16,520	Qty. per 40' container	33,040	Qty. per 40' HQ container	37,040
Packaging	1	Gift Box																							
Qty per export carton	20 pcs	Pieces																							
Gift box meas.:	160 x 55 x 11	MM																							
Meas. per export carton	355 x 295 x 31	MM																							
G.W:	8.1	Kgs																							
N.W:	7.6	Kgs																							
Qty. per 20' container	16,520																								
Qty. per 40' container	33,040																								
Qty. per 40' HQ container	37,040																								

Remark: 1.Payment term is 30%T/T
2.Warranty is 12 monthes
3.Delivery time is 25-30days for 1000pcs.